

<u>Inflatable Pipe Stoppers</u>

Sizes: 2 to 80" (50 to 2035 mm)

GBC Ltd offer a range of shapes and sizes of inflatable stoppers, suitable for all applications. Made from a natural rubber bladder covered in waterproof polyurethane coated nylon to prevent friction and static electricity build up.

Types of Pipe Stopper

Cylindrical

These are generally used for blocking pipes where access is restricted.

Spherical

These stoppers have less contact area than cylindrical stoppers, and are most suited to applications where access is further limited. Due to its shape the spherical inflatable stopper can be used at any angel.

Square / rectangular

These stoppers have a variety of applications, including in air conditioning ducting and venting.

Doughnut

These stoppers require minimal space and are perfectly suited to larger diameter pipes as there is less inflation required.

Sausage

The design of this type gives more contact area between the stopper and the pipe wall enabling these stoppers to hold back more pressure.


Heat resistant

These stoppers are made from a specially designed kevlar and nomex mix material to withstand temperatures up to 350°c for applications involving higher temperatures such as pre heating.

Each inflatable stopper comes with an inflation hose fitted with a schrader valve enabling inflation with a standard airline, bicycle or foot pump.

GBC Industrial Tools inflatable stoppers are supplied as standard with no through tube. Through tubes can be supplied when the stoppers are required for weld purging applications.

When deflated, the inflatable stoppers can be inserted and withdrawn with ease.



Part No.	Inflatable Stopper Size	Min ID MM	Max ID MM
IS2	2" (50mm)	45	55
IS3	3" (75mm)	70	80
IS4	4" (100mm)	95	105
IS5	5" (125mm)	120	130
IS6	6" (150mm)	145	155
IS7	7" (175mm)	170	180
IS8	8" (200mm)	195	205
IS9	9" (225mm)	220	230
IS10	10" (250mm)	245	255
IS11	11" (275mm)	270	280
IS12	12" (300mm)	295	305
IS13	13" (325mm)	320	330
IS14	14" (350mm)	345	355
IS15	15" (375mm)	370	380
IS16	16" (400mm)	395	405
IS17	17" (425mm)	420	430
IS18	18" (450mm)	445	455
IS19	19" (475mm)	470	480
IS20	20" (500mm)	495	505
IS21	21" (525mm)	520	530
IS22	22" (550mm)	545	555
IS23	23" (575mm)	570	580
IS24	24" (600mm)	595	605
IS26	26" (650mm)	645	655
IS27	27" (675mm)	670	680
IS28	28" (700mm)	695	705
IS30	30" (750mm)	745	755
IS32	32" (800mm)	795	805
IS34	34" (850mm)	845	855
IS36	36" (900mm)	895	905
IS39	39" (1000mm)	995	1005
IS44	44" (1100mm)	1095	1105
IS48	48" (1200mm)	1195	1205
IS51	51" (1300mm)	1295	1305
IS55	55" (1400mm)	1395	1405
IS60	60" (1500mm)	1495	1505
IS63	63" (1600mm)	1595	1605
IS67	67" (1700mm)	1695	1705
IS71	71" (1800mm)	1795	1805
IS75	75" (1900mm)	1895	1905
IS79	79" (2000mm)	1995	2005
IS80	80" (2035mm)	2030	2040