

## **RPS6 Heavy Duty Roller Stands**

These heavy duty stands are designed to be either floor or bench mounted. Available with 4 head styles to suit pipes from 4" to 48"

Part No.	Head Style	Load capacity KG/LBS	Weight KG/LBS
RPS6B	Base unit only	N/A	5.8/13
SWK6	Pair steel wheel heads	2,200/4,850	3.4/7
NWK6	Pair nylon wheel heads	450/990	2.2/5
BTK6	Pair ball transfer heads	650/990	3.8/8
FTK6N	Pair feed through roller - Nylon	450/990	3.5/6
FTK6S	Pair feed through roller - Steel	2,200/4,850	3.8/8






## PJ8 Floor Mounted Roller Stand

Part No.	Description	Max diameter	SWL KG
PJ8-1	Feed through roller stand nylon	711 - 315mm	
PJ8-2	Feed through roller stand	250 - 630mm	1000
PJ8-3	Feed through roller stand - Adj Width	500 -1200mm	1000
PJ8-5	Feed through roller stand - 2 tonne	1500mm	2000

## Features and advantages



- Differing trench widths accommodated
- Multi positional
- Rubber coated rollers minimise pipe damage
- Three sizes available to suit pipes from 63mm to 1200mm

## Pipe Buggy



Part No.	Height	Width	Width between wheels	Length	Weight
PB1	21" / 53cm	28" / 71cm	16" / 41cm	28" / 71cm	31.8" / 82cm

The Pipe Buggy offers a safe method of handling and moving pipes around the workshop or site easily, avoiding damage to the pipe as a result of it being dragged along the ground.

At only 31.8kg / 70lbs it is a light weight yet robust solution to pipe handling problems. With its innovative handle and ratchet strap it allows the operator to lift the pipe from the floor onto the buggy with minimal effort.the Vee Head of the PJ1 Stand to suit varying applications.